

**Technical Data Sheet****sarmac Road Curb Paint****Product**

(Sarmac road curb paint) Top quality road curb paints

Manufacture

sarmac | Safety Road Materials Co. , CPC Industrial compound, Zone (D) , Str. no. (2), Factory no.(17), 6th October , Egypt –Tel. : +(202) 386 42007, Fax : + (202) 386 42008 -P.O.Box : 105 / 12573

Description

Sarmac road curb paint is superior synthetic matt based on high quality alkyd resin and selected additives to exhibit special characteristic.

Usage

Recommended for road curbs road and sidewalks on all new or old surfaces such as cement surface, Apply curb paint to renew and protect old damaged weathered curbs
It's suitable for high way, airplane and garden.

Features

- Good hiding power
- High durability
- Given smooth finish
- Fast dry

Technical Specifications

Color	White	Yellow	Black
Finish	Gloss	Gloss	Gloss
Solid content by weight(± 3)	74	74	74
Specific gravity	1.6	1.6	1.4
Viscosity @25 °C (± 7)	90 KU	90 KU	80 KU
Thinner type	White Spirit	White Spirit	White Spirit

White (RAL 9016)

Blue (RLA 5017)

Gray (RAL 7042)

Black (RAL 9017)

Red (RAL 3020)

Yellow (RAL 1023)



Notes: We can custom match any color for road curb paint.

Custom gray concrete color curb paint, gives old concrete a natural new concrete look.

Usage Conditions

Must be applied under good ventilations area, ambient air must be free of dust during use and drying.

Surface preparation

The surface must be clean from dust oil and grease.

The surface of curb should be flat

Apply concrete sealer to the edging with a paint brush before applying the curb paints.

Drying time @25 °C

Initial drying time: 1.5 h

Recoating time: 5 h

Final drying time: 12 h

Tools

Spray gun, Bruch or roller

Storage & Validity

Keep the sealed original drum at good ventilation place away from direct sun light and heat. The product validity is 12 month from production date.

Packaging

Drum: 25 Kg